



Recycled Low Melt Co-PET/PET Fiber

Layo offers all specifications of Recycled Low Melt Co-PET/PET Fiber which is major binder material in nonwoven industrial. In the past two decades, we had accumulated many clients around the world, which provided continuous orders to suppliers, and we always keep the balance among suppliers-Layo-customers, with this policy, all of us are getting closer and gaining more trust.

LAYO is a professional China **Recycled Low Melt Co-PET/PET Fiber** manufacturer and supplier, if you are looking for the best **Recycled Low Melt Co-PET/PET Fiber** with low price, consult us now! LAYO adhered to the principle of "quality is the life", to provide customers with the best quality, the most competitive prices, the first-class after-sales service.

China based supplier of **Recycled Low Melt Co-PET/PET Fiber**: sheath/core concentric structure based bicomponent fiber, its low melt sheath CoPET is a modified polyester with melting point 110°C, while core is normal polyester with MP-265°C.

GRS certificate is available, in order to meet with our customers' sustainability goal.

Product Technical Indicators

Standard TDS of 4den 38mm Standard **Recycled Low Melt Co-PET/PET Fiber**

Characteristic	Unit	Min	Max	Test Method	Remark
Linear Density	dtex	4.4	4.67	GB/T14335-2008	
Cut length	mm	37	39	GB/T14336-2008	
Tenacity at peak	cn/dtex	2.6	3.1	GB/T6504-2017	
Elongation at peak	%	40	80	GB/T14337-2008	
Crimp n.	n./inch	10	12	GB/T14328-2008	Adjustable
Spin finish	%	0.3	0.4	GB/T6504-2017	Adjustable

Product Specification Details, And Precise Application

China based supplier of **Recycled Low Melt Co-PET/PET Fiber** It is an ideal fiber for thermal bonding nonwoven fabrics which are widely used for automobile, hygiene etc. Below the specification range:

Fiber denier: 2dn ~ 6dn,

Main cut length: 38mm or 51mm

Luster: raw white/semi dull or full dull,

Spin finish: standard finish or hydrophilic finish

Product Production And Delivery Display Diagram

